

Index

- Amplifier, negative-resistance, 61, 68, 72
 - nonunilateral, 66, 71
 - parametric, 73
 - two-terminal-pair, classification of, 59
 - $U < 0$, 72
 - unilateral, 71
 - unilateral $U > 1$, 71
 - wideband, 74
- Amplifier cascade, 2
- Amplifier noise performance, criterion for, 5
- Amplifiers, interconnection of, 55
- Available power, 14

- Becking, A. G. Th., 46, 47
- Belevitch, V., 33

- Canonical form, 31
 - derivation of, 28
- Cascading, problem of, 3
- Characteristic-noise matrix, eigenvalues of, 23
 - general formulation of, 38
 - impedance formulation of, 22
 - mixed voltage-current formulation of, 41
 - trace of, 23
- Circulator, 69, 72
- Classification of networks and eigenvalues, 24
 - in \mathbf{T} -matrix representation, 40
- Classification of two-terminal-pair amplifiers, 59
- Cross-power spectral densities, 10

- Dahlke, W., 46, 47

- Eigenvalues, 22
 - classification of, 24
 - least positive, 53
- Excess-noise figure, 48
 - lower limit imposed on, 53
- Exchangeable power, 15, 44
 - matrix form for, 19
 - matrix formulation of, 44
 - n -terminal-pair networks, 15
 - stationary values of, 22
- Exchangeable-power gain, 43, 46
 - algebraic signs of, 49
- Extended noise figure, 43, 46

- Feedback, 3
 - lossless, 54
- Franz, K., 2
- Friis, H. T., 2

- Gain, available, 43
 - exchangeable-power, 43, 46

- Gain, extended definitions of, 43
 unilateral U , 59
- General-circuit-parameter representation, 36, 61
- Granlund, J., 17, 74
- Grid-noise resistance, 66
- Groendijk, H., 46
- Gyrator, lossless, 59
- Hermitian conjugate, 11
- Hermitian matrix, 11
- Imbedding, 12
 lossless, 20
 passive dissipative, 57
 reciprocal, 59
- Impedance representation, 6, 9, 38
- Indefinite matrix, 16, 52
- Interconnection of amplifiers, lossless, 6, 54
 passive dissipative, 55
- Invariants, 25, 31
- Knol, K. S., 46
- Lossless circulator, 69
- Lossless feedback, 54
- Lossless gyrator, 59
- Lossless imbedding, 20
- Lossless interconnection, 54
- Lossless transformation, 9, 12, 19, 61
- Losslessness, condition of, 13
- Maser, 7, 68
- Mason, S. J., 3, 59, 61
- Matrix, characteristic-noise, 22, 38, 41
 general-circuit, 61
 general representation, 34
 Hermitian, 11
 impedance, 9
 indefinite, 16, 52
 negative definite, 16, 52
 noise column, 47, 61
 permutation, 45
 positive definite, 11, 16, 52
 scattering, 69
 semidefinite, 11, 16
 T , 34, 39, 40
- Matrix formulation, of exchangeable power, 44
 of exchangeable-power gain, 45
 of extended noise figure, 46
- Matrix formulation, of stationary-value problem, 19
- Mismatch, input, 6, 54, 61, 71
- n -to- n -terminal-pair network transformations, 6, 25
- n -to-one-terminal-pair network transformation, 6, 18
- Negative definite matrix, 16, 52
- Network transformations, n -to- n -terminal-pair, 6, 25
 n -to-one-terminal-pair, 6, 18
- Networks, classification of, 14, 24, 40
 in thermal equilibrium, 25
 pure-noise, 47
 with coherent sources, 25
- Noise column matrix, 47, 61
- Noise figure, excess, 48
 extended, 43, 46
 matrix formulation of, 46
- Noise measure, 4, 42, 48
 allowed ranges of, 49
 for conventional low-frequency vacuum tube, 66
 for triode, 66
 optimum ($M_{e,opt}$), 54, 55
- Noise parameter p_T , 39
 in mixed voltage-current representation, 41
- Noise performance, criterion for amplifier, 5
 optimization of, 61, 68
 single-frequency, 1, 73
 spot, 1
- Nonreciprocal transformations, 59
- Nonunilateral amplifier, 66, 71
- Optimization, of amplifier, indefinite case, 61
 of maser amplifiers, 71
 of negative-resistance amplifiers, definite case, 68
- Optimum noise measure ($M_{e,opt}$), 54, 55
 for low-frequency vacuum tube, 66
- Parametric amplifier, 73
- Passive dissipative imbedding, 56
- Passive dissipative interconnection of amplifiers, 56
- Passive network at equilibrium, 26
- Permutation matrix, 45
- Positive definite matrix, 11, 16, 52
- Power, available, 14
 exchangeable, 15, 44

- Power spectral densities, 11
- Reciprocal imbedding, 59
- Reduction of number of terminal pairs, 32, 56
- Robinson, F. N. H., 3
- Rothe, H., 46, 47
- Scattering-matrix representation, 69
- Self-power spectral densities, 10
- Semidefinite matrix, 11, 16
- Signal-to-noise ratio, 1, 73
- Single-frequency noise performance, 1, 73
- Spectral densities, cross-power, 10
 - power, 11
 - self-power, 10
- Spot-noise figure, 2
- Stationary-value problem, eigenvalue formulation of, 21
 - matrix formulation of, 19
- Stationary values of exchangeable power, 22
- T-matrix representation, 34, 39, 40
- Terminal-voltage and current vector, 38
- Thévenin representation, 14
- Trace of characteristic-noise matrix, 23
- Transformation, lossless, 9, 12, 19, 61
 - n -to- n -terminal-pair network, 6, 25
 - n -to-one-terminal-pair network, 6, 18
- Transformation from one matrix representation to another, 35
- Transformation network, 12
- Transistor amplifiers, 59
- Twiss, R. Q., 26
- Unilateral amplifier, 71
- Unilateral amplifier with $U > 1$, 71
- Unilateral gain U , 59
- Vacuum tube, 59, 66
- van der Ziel, A., 2, 68
- Vector, noise column, 47, 66
- Wideband amplifiers, 74