

Index

- Abrasion of skin before electrode
 - placement, 120
- Absolute voltages, 103
- AC current, 336
 - oscillations in, 113
- Accessories in ERP lab, 309–310, 311b–312b
- Action potentials, 23, 27–29
- Active electrodes, 101–104, 105f
- Adjacent response (ADJAR) filters for overlap, 149
- Adrian, E. D., 3
- Advantages of ERP technique, 21–22, 34
- Ag/AgCl electrodes, 117
- Aine, C., 276, 293
- Alcaini, M., 39
- Aliasing, 127, 177
- Alpha waves, 164f, 168–169
 - measurements of, 156
 - noise from, 177, 317
 - as noise source, elimination of, 213
- Amperes, 333
- Amplifiers
 - blocking of, 164f, 167–168
 - calibrator for, 310
 - and common mode rejection, 120–121
 - differential, 103
 - electrode-amplifier-computer connections, 307–308
 - filters in, 113
 - gain setting on, 125, 128
 - headbox for, 308
 - high-pass filter setting on, 125–126
 - input impedance of, 121
 - recommended types of, 314–315
 - saturation of, 167–168
- Amplitude
 - area, 139, 229–230
 - attenuation by filters, 178–181
 - of frequencies, 187–191
 - half-amplitude cutoff, 179, 180, 314, 321
 - and latency variability problem, 135–139
 - local peak, 231, 341n
 - mean, 229, 234–235. *See also* Mean amplitude
 - measurements of, 57, 229–237, 229f
 - in oscillations, 142–143
 - of P3 component, factors affecting, 43–44
 - peak, 139, 229, 230–234. *See also* Peak amplitude
 - peak-to-peak, 237. *See also* Peak-to-peak amplitude
 - relation to latency, 52, 53f, 55–56
- Analog filters, 176
- Analog-to-digital converters (ADC), 125, 315
 - sixteen-bit, 126
- ANOVA, 250–254. *See also* Statistical analyses
- Anterior cingulate cortex, 47
- Area amplitude, 13, 229–230
- Area-based measures compared to peak-based, 139–140
- Arnell, K. M., 87, 88
- Artifact(s), 12
 - aliasing, 127, 177
 - in low-pass filtered waveforms, 209, 210f
 - oscillations caused by filters, 183f, 184
 - peaks added by filters, 179
 - stimulus-related, 324
 - tearing, 328
- Artifact correction, 152, 170–173
 - problems with, 172–173
- Artifact rejection, 101, 151–170, 321, 340n
 - alpha waves, 164f, 168–169
 - amplifier saturation or blocking, 164f, 167–168
 - choice of sensitive measure, 154

- Artifact rejection (cont.)
 in electrooculograms, 154–155, 155f
 eye movements, 162–166
 eyeblinks, 158–162
 and filtering before or after averaging,
 219, 340n–341n
 general process, 152–154
 muscle and heart activity, 169–170
 slow voltage shifts, 166–167
 threshold choice, 157–158
 for between-subject studies, 157
 for individual subjects, 158
- Assumptions
 ANOVA, violation of, 250, 258–260
 averaging, 134–135
- Attention
 auditory selective, 75–80, 77f, 340n
 and locus of selection, 75
 and physical stimulus confounds, 70b–
 71b
 systems in detection of color and motion,
 13–17
- Attention effects, 297b
- Attentional blink paradigm, 87–88, 88f
- Auditory brainstem responses, 7
- Auditory selective attention, 75–80, 77f,
 340n
- Auditory sensory responses, 38–39
- Auditory stimuli
 artifacts from, 324
 timing of, 323
- Automation of processing, 321
- Average across all electrodes as reference,
 109–111, 110f
- Average mastoids reference deviation,
 107–108
- Averaging, 131–151
 application of, 132f
 assumptions in, 134–135
 basic procedures in, 9–10, 12, 131–135
 of dipole orientations, 31
 distortions caused by, 56–57
 electrooculogram waveforms in, 165–166
 and filtering before or after artifact
 rejection, 219
 grand averages in, 17–21, 27. *See also*
 Grand averages
 and latency variability problem, 135–139,
 136f, 138f
 area measures in, 139–140
 response-locked averages in, 140
 time-locked spectral averaging in, 142–
 145, 144f
 Woody filter technique in, 141–142
 and noise in waveforms, 131, 133
 on-line, 317
 and overlap problem, 145–149, 146f
 in transient and steady-state responses,
 149–151, 150f
 reliability of, 18–20, 19f
 residual EEG noise in, 99
 response-locked, 138f, 140, 307, 320
 baselines in, 237
 signal-to-noise ratio in, 133–134
 stimulus-locked, 138f, 140
 time-locked, for spectral information,
 142–145, 144f
 of voltages at time points, 192f, 193–195
 Axford, J. G., 36
- Background music, use of, 312b
- Baillet, S., 271, 320
- Band-pass filters, 178, 191
- Baselines, 236–237
 prestimulus, 236
 and response-locked averages, 237
- Bayes theorem/Bayesian inference, 294,
 295
- Behavioral response devices, 306–307
- Belliveau, J. W., 285
- Bentin, S., 38
- Bereitschaftspotential, 47
- Berg, P., 171, 172
- Berger, H., 3
- Bertrand, O., 32, 58, 111
- BESA. *See* Brain electrical source
 analysis
- Bessel filters, 215
- Bipolar recordings
 artifacts and noise sources in, 170
 in eye movements, 162
 in eyeblinks, 162
- Blink. *See* Eyeblinks
- Bloch's law, 341n
- Blocking, amplifier, 164f, 167–168
- Blurring of voltage distribution, 32
- BOLD signal, 23
- Boundary element model, 271

- Brain electrical source analysis (BESA), 271–273, 273f. *See also* Equivalent current dipole, localization methods
- Brainard, D. H., 324, 330
- Brainstem evoked responses, 7, 38
auditory, 7, 38
cutoff frequency in, 208
- BrainStorm package for data analysis, 320
- Brandeis, D., 142
- Braren, M., 5
- Bright and dim stimuli, comparative effects of, 71, 73–74, 252, 253f
- Broadbent, D. E., 75
- Brown, C. M., 46
- C1 component, visual, 35–36, 58–59
- Cables, noise from, 114, 116, 305, 308, 312b
- Calibration of recording system, 128–129
- Calibrator for amplifiers, 310, 314
- Capacitance, 117, 336
- Carmel, D., 38
- Carmichael, L., 3
- Cathode-ray tube. *See* CRT monitors
- Causal filters
high-pass, 221f, 222–223
low-pass, 210f, 214–215
frequency response function, 210f, 214–215
impulse response function, 210f, 214
- Chair, recliner, 169, 306
- Chalklin, V., 109
- Channel mapping, 317
- Chelazzi, L., 297b
- Chin rests, 167, 169, 306, 340n
- Chun, M. M., 88
- Clark, V. P., 36, 59
- Clean data, importance of, 86–87, 99–101, 185
- CNV. *See* Contingent negative variation
- Cognitive neuroscience
ERP findings in, 94
reference sites in, 106–108
- Cohen, D., 278
- Coles, M. G. H., 35, 43, 48, 65, 83, 170, 171, 172, 235
- Color-defined targets, detection of, 13–17
- Comerchero, M. D., 42
- Common mode rejection, 120–121, 314
- Communication with subjects in experiments, 311b
- Component-independent experimental designs, 66–94
avoiding confounds and misinterpretations in, 66–74
examples of
auditory selective attention, 75–80, 77f
dual-task performance, 87–94, 88f, 90f
partial information transmission, 80–87, 84f
- Computers, 303–305
for amplifier settings, 315
in artifact detection, 156–157
digitization software, 315–318. *See also* Digitization
electrode-amplifier-computer connections, 307–308
event codes for, 305
software for. *See* Software
- Conductance, 334
- Conduction, volume, 32
- Confounds
avoidance of, 66–74
examples of, 70b–71b
- Constraints, 281–283, 283f
and minimum norm solution, 283–286
- Context updating hypothesis, 42–43
- Contingent negative variation, 4–5, 49
- Continuous performance task, 7
- Continuous recording, 316
- Contralateral sites, N2pc component in, 15–17, 41, 65
- Converging evidence, 296–297, 297b
- Convolution
mathematical properties of, 215–216
and noise affecting latency measures, 241
in time domain, 197–199, 198f, 200, 201–203, 202f
equivalent to multiplication in frequency domain, 200–201, 201f, 216
of unity impulse response function, 217
- Cortical folding patterns, 20, 31
- Cortically constrained distributed source localization, 281–283, 283f
- Costa, L. D., 47
- Costs of recording techniques, 24, 26
- Courchesne, E., 42

- CRT monitors, 324–332
 basic operation of, 325–327, 326f
 compared to LCD monitors, 330–332
 timing in, 324, 327–329
 errors of, 328–329
- Cuffin, B. N., 278, 298
- Curran, T., 38
- Current, electrical, 333–334
 alternating (AC), 336
 direct (DC), 335
- Current density, 111–112
- Current source density (current density),
 111–112
- Cutoff frequency, 177, 186, 314
 for brainstem evoked responses, 208
 and digitization rate, 127, 177
 half-amplitude, 179, 180f, 314, 321
 in gaussian filter, 212–213
 in high-pass filters, 125
 in low-pass filters, 127–128, 208
 and sampling rate, 128
- Dale, A. M., 285
- Data acquisition system, 303–318, 304f
- Data analysis systems, 318–322
 suggested features in, 320–322
- Davis, H., 2, 4, 10b
- Davis, P. A., 4, 10b
- DC current, 335
- DC recordings, 185
 in saccades, 163, 166
- Deblurring, 32
- Deecke, L., 47
- Definition of ERP component, 58–59
- Dehaene, S., 47, 86b, 94
- de Jong, R., 86b
- Delays between stimuli, and overlapping
 waveforms, 147, 148
- Delorme, A., 319
- Desimone, R., 297b
- Desmedt, J. E., 109
- Deutsch, D., 75
- Deutsch, J. A., 75
- Dien, J., 111
- Difference waves
 to isolate components, 63–65, 298–299
 and isolation of lateralized readiness
 potential, 83
 for overlap problems, 91, 94–95, 247
- Differential amplifiers, 103
- Differential step function in eyeblink
 artifact rejection, 162
- Digital filters, 176
 convolutions in, 201–203, 202f
 equation for, 193, 195
 impulse response functions in, 196
 lack of phase shift with, 181
- Digitization, 124–126
 event codes in, 305, 315
 filters in, 181, 182, 185
 rate of, and cutoff frequency of filter, 127,
 177
 software for, 315–318
 testing of, 317–318
- Dipoles
 equivalent current, 31, 269
 forward problem, 268
 inverse problem, 33–34, 269
 modeling procedures to isolate ocular
 activity, 172
 neuron, 29
 summation of, 31
 seeded, 276
- Direct coupled (DC) recordings, 126
- Di Russo, F., 36, 150f, 272, 274f
- Disadvantages of ERP technique, 22–23, 26
- Distortions
 from averaging, 56–57
 from filters, 170, 175, 182–185, 183f,
 204–223
- Distributed source localization methods,
 269, 281–289
 added value of magnetic recordings, 286–
 289, 287f
 cortically constrained models, 281–283,
 283f
 minimum norm solution, 283–286
- Donchin, E., 9b, 42, 43, 44, 58, 94, 170,
 171, 172, 262
- Double filtering, frequency response
 function of, 216
- Dual-task performance, study of, 87–94,
 88f, 90f
- Duncan-Johnson, C. C., 22, 43
- Earlobe reference sites, 106–107, 308
- Early selection hypothesis, 75–79
- Earth as reference point, 102

- Edge detection algorithms for artifact detection, 165
- EEG. *See* Electroencephalogram
- EEGLAB package for data analysis, 319–320
- Eimer, M., 41
- Electrical activity in neurons, 27–32
- Electrical noise in environment, 112–116, 305, 306, 308, 309
 - filtering of, 182
 - low-pass filters in, 208
- Electrical potential, 40, 101–104, 333
- Electricity
 - basic principles of, 333–337
 - relation to magnetism, 336–337, 336f
- Electrocardiogram (EKG) artifacts, 164f, 170
- Electrode(s), 116–124
 - active, 101–104, 105f
 - caps for, 313
 - in geodesic sensor net, 122
 - ground, 102, 103
 - interactions between condition and electrode site, 254–258, 256f
 - large arrays of, 121
 - perspective on, 123–124, 124b
 - problems with, 122
 - placing and naming of sites in 10/20 system, 118b–119b
 - recommended types of, 313
 - reference, 103, 104–112, 105f, 308
 - silver/silver-chloride, 117
 - tin, 117
- Electrode-amplifier-computer connections, 307–308
- Electroencephalogram (EEG)
 - amplifier settings, 125–126
 - blocking and skin potential artifacts in, 164f, 169
 - fields compared to MEG fields, 286–288
 - flat-line signal from slow voltage shifts, 125, 167, 168
 - historical aspects of, 3–4
 - residual noise in, 99
- Electromotive force, 333
- Electromyogram (EMG), 164f, 169, 306
- Electrooculogram (EOG)
 - artifact corrections, 171
 - artifact rejections, 154–155, 155f, 157
 - averaged waveforms, 165–166
 - eyeblink detection, 158–160, 159f
 - in saccades, 163, 164f
 - voltages produced by eye movements, 163
- EMG. *See* Electromyogram
- Endogenous components, 11
- EOG. *See* Electrooculogram
- Epoch-based recording, 316
- Equivalent current dipole, 31
 - localization methods, 269, 271–280, 293–294
 - BESA technique in, 271–273, 273f
 - multi-start approach in, 276, 294
 - numbers and locations of dipoles in, 273–276
 - operator dependence of, 275, 277
 - shortcomings of, 276–278
 - simulation study of, 278–280, 341n
 - source waveforms in, 273, 274f
- Eriksen, C. W., 80, 296
- ERMF. *See* Event-related magnetic fields
- ERPology, 5–6
- Error detection, 46–47
- Error-related negativity, 47
- Event codes, 305, 315
 - timing of, 322–324
- Event-related magnetic fields (ERMFs), 23, 24t, 33, 286, 299
 - combined with ERP data, 286–289
- Event-related potentials (ERPs)
 - advantages and disadvantages of, 21–23
 - combined with magnetic data, 286–289
 - compared to other measures, 23–27, 24t
 - components of, 34–49, 59–61
 - definition of, 58–59, 339n–340n
 - history of, 3–7
 - origin of term, 4, 6–7
 - steady-state, 150–151, 150f
 - transient, 149–150, 150f
- Evoked potentials (EPs), 6
- Evoked response, 7
 - brainstem, 7, 38, 208
 - visual, 7
- Exogenous components, 11
- Experiment design and interpretation
 - ambiguities avoided in, 61–66
 - component-independent designs in, 66
 - confounds and misinterpretations in, 66–71

- Experiment design and interpretation (cont.)
 - avoidance of, 72–74
 - definition of ERP component in, 57–61
 - examples of, 75–94
 - focus in, 62
 - isolation of components in, 63–65
 - large components in, 63
 - rules for, 52–57, 74, 92, 96–97
 - strategies for, 62–66, 94–95, 98
 - waveform peaks *versus* latent ERP components in, 51–57
 - well-studied components used in, 62
- Experimental effect compared to raw ERP waveforms, 55
- Experimentwise error, 252
- Eye movements
 - artifact correction, 170–173
 - detection and rejection of artifacts, 162–166
 - suppressed during recordings, 311b
- Eyeblinks, 12
 - artifact correction, 170–173
 - assessment with electrooculogram, 154–155, 155f
 - attentional blink paradigm, 87–88, 88f
 - detection and rejection of artifacts, 158–162
 - differential step function in, 162
 - step function in, 161
 - polarity reversal in, 159–160, 159f, 161
 - reducing occurrence of, 160
 - suppressed during recordings, 311b
 - and voltage deflection levels, 153–154
- Face stimuli, N170 wave in, 37–38
- Falkenstein, M., 47
- Falsification, 295
- Fan, S., 36, 59, 94
- Faraday cage, 114, 115f, 305, 310
- Felleman, D. J., 340n
- Ferree, T. C., 123
- 50-Hz noise, 113
- 50 percent area latency measure, 139, 239–242, 240f
 - compared to median reaction time, 246
 - disadvantages of, 242
- Filter(s)
 - adjacent response (ADJAR), 149
 - and amplitude attenuation, 178–181
 - analog, 176
 - attenuating low frequencies, 177–178
 - band-pass, 178
 - frequency response functions, 191
 - Bessel, 215
 - causal
 - high-pass, 221f, 222–223
 - low-pass, 210f, 214–215
 - cutoff frequency of, 177, 186, 314. *See also* Cutoff frequency
 - digital, 176
 - lack of phase shift with, 181
 - distortions from, 170, 175, 182–185, 183f, 204–223
 - with high-pass filters, 219–223
 - with low-pass filters, 207–215, 210f
 - with notch filters, 204–207, 206f
 - frequency-domain, 175
 - transformed into time domain, 188f, 190
 - frequency response function, 179, 180f, 188f, 190
 - gaussian, 210f, 212–214. *See also* Gaussian filters
 - half-gaussian, 21
 - high-pass, 178, 314
 - to attenuate low frequencies, 195
 - avoidance of, 187
 - causal, 221f, 222–223
 - cutoff frequency, 125
 - distortions from, 219–223
 - in eye movement recordings, 163
 - frequency response function, 179, 191
 - gaussian, 218f, 219–220, 221f
 - linear, 219
 - noncausal, 222
 - for overlap problem, 149
 - reducing slow voltage shifts, 167, 178
 - settings for, 125–126
 - time constants, 179, 180f, 181
 - time-domain implementation of, 216–219
 - windowed ideal, 220, 221f
- impulse response. *See also* Impulse response function
 - finite, 175, 200
 - infinite, 200
 - and latency shift, 181
 - line-frequency, 113, 182, 186, 208

- low-pass, 127–128, 178, 314
 - causal, 210f, 214–215
 - compared to mean amplitude measures, 234
 - cutoff frequency, 127–128, 208
 - distortions from, 207–215, 210f
 - frequency response function, 179, 191
 - noncausal, 214
 - windowed ideal, 208–209, 210f, 213
- need for, 176–178
- noncausal
 - high-pass, 222
 - low-pass, 214
- notch, 178, 182, 186, 315
 - frequency response functions, 191
 - temporal distortions from, 204–207, 206f
- phase response function, 179
- recursive, 200
- running average, 210f, 211–212, 213–214
- settings for, 125–126, 315
- suppressing high frequencies, 177
- time-domain, 175
 - distortions from, 204–223
- transfer function, 178–179
- windowed ideal, 208–209, 210f, 213, 220, 221f
- Filtering, 175–224
 - as frequency-domain procedure, 187–193, 188f
 - problem with, 191–193
 - and peak amplitude measures, 232
 - recommendations for, 181, 185, 186–187, 223–224
 - as time-domain procedure, 193–200, 194f
 - Woody technique, 141–142
- Finite element models, 270–271
- Finite impulse response filters, 175
- Flat-line signal in EEG, in slow voltage shifts, 125, 167, 168
- fMRI
 - activation centers in, 276
 - BOLD signal in, 23
 - compared to ERP source localization, 290–291
 - compared to event-related potentials, 16
 - compared to other recording techniques, 24t, 267
 - correspondence with ERP data, 285
 - spatial gaussian filters in, 212
- Folds, cortical, 20, 31
- Foolproof techniques, 34
- Forward problem, 33, 268
- Forward solution, 269–271
 - boundary element model in, 271
 - finite element models in, 270–271
- Fourier analysis, 58, 187
 - transient waveforms represented in, 192
- Fourier transform, 143, 189, 200–201, 340n
 - in detection of EMG activity, 169
 - inverse, 189, 201, 201f
- Fractional area latency, measurement of, 239–242, 240f, 248
- Frame buffers in video cards
 - in CRT monitors, 325, 329
 - in LCD monitors, 330
- Frequencies
 - amplitude of, 187–191
 - cutoff. *See* Cutoff frequency
 - phases of, 191
- Frequency domain, 317
 - relation to time domain, 182, 184, 187, 200–204, 201f, 202f
 - and distortion from filters, 192–193
- Frequency-domain filters, 175, 187–193, 188f
 - problem with, 191–193
- Frequency response function of filters, 179, 180f, 188f, 190
 - with causal filters, 214–215
 - with double filtering, 216
- Friston, K. J., 285
- Full width at half maximum (FWHM), in gaussian function, 212–213
- Functional magnetic resonance imaging. *See* fMRI
- FWHM. *See* Full width at half maximum
- Gain settings on amplifiers, 125, 128
- Galambos, R., 2, 4, 10b, 42, 149, 162
- Ganis, G., 38, 45
- Garner, W. R., 296
- Gasser, T., 171, 172
- Gaussian filters
 - high-pass, 218f, 219–220, 221f
 - low-pass, 210f, 212–214
 - frequency response function, 210f, 212
 - full width at half maximum value, 212

- Gaussian filters (cont.)
 impulse response function, 210f, 212
 temporal distortion from, 213–214
- Gaussian impulse response functions, 321
 and noise affecting latency measures, 241
- Gauthier, I., 38
- Gazzaniga, M. S., 46
- Gehring, W. J., 46, 47
- Generator site changes, effects of, 255–257
- Geodesic sensor net, 122
- George, J. S., 285, 294
- George, N., 38
- Gevens, A., 32
- Gibbs, F. A., 3
- Girelli, M., 13, 70b
- Glaser, E. M., 175
- Go/No-Go trials, and lateralized readiness potential, 81, 84–85
- Gorodnitsky, I. F., 172
- Grand averages, 17–21, 27
 with bright and dim stimuli, 253f
 and mean amplitude measures, 235
 and peak amplitude measures, 232, 233
- Gratton, G., 48, 170, 171, 172, 173
- Gray, C. M., 135
- Greenhouse-Geisser epsilon adjustment, 259–260, 341n
- Ground circuit, 102–103
- Ground electrode, 102, 103
- Gustatory responses, 40
- Hackley, S. A., 39, 80–86
- Hagoort, P., 46
- Hake, H. W., 296
- Half-amplitude cutoff, 179, 180f, 314, 321
 in gaussian filter, 212–213
- Half-gaussian filters, 221f, 222
- Hämäläinen, M. S., 283, 284
- Hansen, J. C., 100–101, 168, 239, 248, 340n
- Hansen's axiom, 100, 112, 152, 185–187, 208, 213
- Headbox, 308
- Headphones, shielding of, 324
- Heart activity, detection of, 164f, 169
- Heffley, E. F., 58, 262
- Heinze, H., 276, 297b
- Helmholtz, H., 34, 269
- Heterogeneity of variance and covariance, 259
- High-pass filters. *See* Filter(s), high-pass
- Hijacking ERP components, 94–95
- Hillyard, S.
 on auditory selective attention, 75–80
 on C1 wave, 36, 59
 on converging evidence, 297b
 on eye movements, 162
 on 50 percent area latency, 242
 on fractional area latency, 239, 248
 on hijacking ERP components, 94
 on impedance of skin, 121
 laboratory at UCSD, 2, 10b, 100
 on language-related components, 45, 46
 on latency jitter, 135
 on mismatch negativity, 39
 on modality-specific P3 wave subcomponents, 35
 on N1 wave, 37
 on N2 family, 40, 41
 on N2pc component, 14
 on overlap patterns, 148, 149
 on P3 family, 42
 on replication of results, 251b
 on slow voltage shifts, 167
 on steady-state ERPs, 151
 on subtle confounds, 70b
 on target letter shapes, 68
 on transient responses, 150f
- Hillyard principle, 68–69, 74, 97
- Holcomb, P. J., 45, 46
- Holroyd, C. B., 47
- Homogeneity-of-covariance assumption, 258–259
- Hopf, J.-M., 37, 287f, 297b
- Hopfinger, J. B., 149, 151
- Huang, M., 276, 293
- Humphries, C., 172
- Ideal filters, windowed
 high-pass, 220, 221f
 low-pass, 208–209, 210f, 213
- Ignored stimuli
 processing of, 22
 responses to, 75–77
- Ikui, A., 40
- Ilmoniemi, R. J., 283, 284, 286
- Impedance, 117–119, 314, 335–336

- and common mode rejection, 120–121, 314
- measurements of, 119
- problems from, 120–122
- reduction of, 119–120
- and signal quality with high-impedance systems, 122–123
- and skin potentials, 121
- Impedance meter, 309–310
- Impulse response filters
 - finite, 175, 200
 - infinite, 200
- Impulse response function, 196–200, 198f, 321
 - of causal filters, 214
 - convolution in time domain, 197–199, 198f, 200, 201–203, 202f
 - gaussian, 321
 - high-pass, 218f, 219–220, 221f
 - and noise affecting latency measures, 241
 - high-pass
 - creation of, 217–219, 218f
 - gaussian, 218f, 219–220, 221f
 - unity, 217, 218f
- Independent components analysis (ICA), 58, 60, 242, 263
 - in artifact correction, 172
- Inductance, 117
- Inference, strong, 295
- Interactions with electrode site, 254–258, 256f
- Intercom system, 310
- Interrupt
 - vertical retrace, 328
 - video blanking, 328
- Invasiveness of recording techniques, 24–25, 24t
- Inverse Fourier transform, 189, 201, 201f
- Inverse problem, 33–34, 269
 - minimum norm solution in, 285
- Ipsilateral waveforms, N2pc component in, 15–17
- Isreal, J. B., 44
- Ito, S., 47
- Jackknife technique to measure onset
 - latency differences, 249
- Jaskowski, P., 42
- Jasper, H. H., 3, 118b
- Jeffreys, D. A., 36, 37
- Jennings, J. R., 259
- Jitter, latency. *See* Latency, variability of
- John, E. R., 5
- Johnson, R., Jr., 43, 44, 58
- Joyce, C. A., 166, 172
- Jung, T. P., 172
- Keppel, G., 258
- Klem G. H., 119b
- Knight, R. T., 42
- Kok, A., 18, 43
- Koles, Z. J., 292
- Kopell, B. S., 22
- Kornhuber, H. H., 47
- Kramer, A. F., 61, 225
- Kutas, M., 38, 43, 44, 45, 46, 62, 94, 172, 257
- Labeling conventions for ERP components, 10–11, 35
- Laboratory setup, 303–332
 - accessories, 309–310, 311b–312b
 - amplifier types, 314–315
 - behavioral response input devices, 306–307
 - computers, 303–305
 - data acquisition system, 303–318, 304f
 - data analysis system, 318–322
 - digitization software, 315–318
 - electrode-amplifier-computer connections, 307–308
 - electrode types, 313
 - recording chamber, 309
 - seating, 305–306
 - stimulus presentation system, 322–332
- Language comprehension
 - assessment of, 22
 - and semantic mismatch
 - in attentional blink paradigm, 89
 - difference waves in, 54
- Language-related ERP components, 45–46
 - and N400 component in word identification, 89–93
- Latency
 - 50% area, 139
 - fractional area, 239–242, 240f, 248

- Latency (cont.)
 and labeling problems, 35
 local peak, 238
 measurements of, 57, 237–249
 compared to reaction time effects, 243–247, 244f
 onset, 66, 247–249. *See also* Onset
 latency or time
 P3 wave, factors affecting, 44–45
 peak, 22–23, 52, 237–239
 relation to amplitude, 52, 53f, 55–56
 shift caused by filters, 181
 variability of, 135–139, 136f, 139f
- Latent ERP components
 assessment of, 51–57
 avoiding ambiguities and misinterpretations in, 61–74
 examples of, 53f
- Lateralized readiness potential (LRP), 48, 65
 isolation with difference waves, 82–83
 and partial information transmission, 80–87
 usefulness of, 86b
- Lawson, D., 117
- LCD monitors, 330–332, 331f
- Leahy, R. M., 271, 278, 298, 299
- Lehmann, D., 284
- Lennox, W. G., 3
- Leuthold, H., 45
- Lewis, P. S., 271
- Lights, electrical noise from, 114
- Lindsley, D. B., 49
- Line-frequency filters, 113, 180f, 182, 186, 208
- Line-frequency noise, 113, 317
- Linear filters, high-pass, 219
- Lins, O. G., 117, 162, 163, 171, 172, 173
- Liu, A. K., 285
- Local field potential recordings, 28
- Local peak amplitude, 231, 341n
- Local peak latency, 238
- Localization methods, 34, 60, 267–300
 distributed source approaches in, 269, 281–289
 equivalent current dipoles and BESA approach in, 269, 271–280
 forward problem and solution in, 268–271
- as model but not measurement of
 electrical activity, 289–292
 and principles of scientific inference, 295–297
 probabilistic approaches in, 292–294
 recommendations for, 294–300
 reporting range of solutions in, 292–294, 293f
- Locus of selection, and attention, 75
- LORETA. *See* Low-resolution
 electromagnetic tomography
- Loveless, N. E., 49
- Low-pass filters, 127–128, 178, 314. *See also* Filter(s), low-pass
- Low-resolution electromagnetic
 tomography (LORETA), 284–285, 298
- LRP. *See* Lateralized readiness potential
- Luck, S. J.
 on advantages of ERPs, 22
 on converging evidence, 297b
 on detection of color and motion, 13
 on difference waves, 64, 65
 on dual-task performance, 89–94
 on 50 percent area latency, 242
 on latency jitter, 135
 on minimum norm solution, 285
 on modality-specific P3 wave
 subcomponents, 35
 on N2 family, 40, 41
 on N2pc component, 14
 on overlap patterns, 149
 on P1 wave, 36
 on P2 wave, 37
 on P3 family, 43, 45
 on reaction times, 246
 on steady-state ERPs, 151
 on subtle confounds, 70b
 on target letter shapes, 68
- Machizawa, M. G., 41
- Magliero, A., 44
- Magnetic fields, 30f, 32–33, 287f
 event-related. *See* Event-related magnetic
 fields
- Magnetic resonance imaging (MRI), 298
 in cortically constrained distributed
 source localization, 282
 functional. *See* fMRI

- Magnetism, relation to electricity, 336–337, 336f
- Magnetoencephalogram (MEG), 33
fields compared to EEG fields, 286–288
- Makeig, S., 58, 143, 172, 319
- Mangun, G. R., 37, 149
- MANOVA, 262
- Mastoid reference sites, 106–107, 308
average mastoids reference derivation, 107–108
linked mastoids reference, 107
- MATLAB program, 148, 319–320, 330
- Matthews, B. H. C., 3
- McCarthy, G., 43, 44, 46, 94, 255, 257
- McClelland, J. L., 80
- McPherson, W. B., 45
- Mean amplitude
compared to peak amplitude, 73
measurement of, 229, 234–235
advantages of, 234–235
compared to low-pass filtering, 234
problems with, 235
- Measuring ERP amplitudes, 229–237, 229f
area amplitude, 229–230
baselines in, 236–237
mean amplitude, 229, 234–235
peak amplitude, 229, 230–234
peak-to-peak, 237
- Measuring ERP latencies, 57, 237–249
compared to reaction time effects, 243–247, 244f
fractional area latency, 239–242, 240f
onset latency, 247–249
peak latency, 237–239
- MEG. *See* Magnetoencephalogram
- Michel, C. M., 284
- Microphones, 310
- Miller, J., 48, 80–86, 248, 249
- Miltner, W., 278
- Minimum norm solution in distributed
source localization, 283–286
combined constraints in, 285
depth-weighted, 284, 298
LORETA technique in, 284–285
- Mirror symmetry of dipoles in simulation
study of BESA, 278–279, 341n
- Mismatch negativity (MMN), 39
- Mismatch, semantic
in attentional blink paradigm, 89
difference waves in, 54
- Models of electrical activity compared to
measurements, 289–292
- Moecks, J., 171, 172
- Monitoring, real-time, 316, 317
- Moore, C. M., 86b
- Moran, J., 297b
- Mosher, J. C., 271
- Motion-defined targets, detection of, 13–17
- Motor ERPs in eyeblinks and eye
movements, 173
- Movement-related components, 48
- Moving-window techniques in time-locked
spectral averaging, 143
- MRI. *See* Magnetic resonance imaging
- Multiphasic waveforms, latency variability
affecting, 136f, 140
- Multiple electrode sites, and ANOVA
results, 254
- Multiple peaks, analysis of, 262–263
- Multiple signal characterization (MUSIC),
271
- Multi-start approach to source localization,
276, 294
- Multi-unit recordings, 28
- Muscle activity
detection of, 164f, 169
low-pass filtering of noise from, 208
post-auricular reflex in, 324
- Music as background in recording, 312
- N1 component, 10–11
auditory, 39, 79
modality-specific, 35
visual, 37
- N2 component, 10–11, 40–41
basic N2, 40
modality-specific, 35
N2a, 41
N2b, auditory and visual, 40, 41
N2pc, 14, 15–17, 41, 65, 297b
isolation of, 15–17
and physical stimulus confounds, 70b–71b
- N10 component, 40
- N170 component, visual (faces), 37–38
- N200 component, 11b
- N280 component, 46

- N400 component, 11b
 - discovery of, 62
 - in dual-task performance, 89–93
 - in experimental manipulations, 61–65
 - in semantic violations, 45–46
 - and word identification, 93
- Näätänen, R., 35, 39, 40, 59
- Nagamine, T., 48
- Naming components, 10–11
- Negative-upward plotting, 9
- Negative variation, contingent, 4–5, 48
- Neurons, electrical activity in, 27–32
- Niese, A., 94
- Noise, 12, 339n
 - affecting peak amplitude measures, 231–232
 - from alpha waves, 177, 317
 - elimination of, 213
 - in averaged waveforms, 131, 133
 - and common mode rejection, 120–121
 - electrode impedance affecting, 123
 - environmental sources of, 112–116, 305, 306, 308, 309
 - filtering of, 180f, 182, 208
 - and 50 percent area latency measure, 241
 - and importance of clean data, 86–87, 99–101, 185
 - in LCD monitors, 332
 - line-frequency, 317
 - filtering of, 113, 180f, 182, 186, 208
 - and onset time, 247
 - and peak latency measures, 238, 241
 - reduction with filters, 177
 - from skin potentials, 121
 - sources of, 100
- Noncausal filters
 - high-pass, 222
 - low-pass, 214
- Nonlinear measures
 - peak amplitude, 232, 233
 - peak latency, 238
- Nonsphericity, 259
- Non-uniqueness problem in distributed
 - source localization, 281–283
- Normalization of data, 257–258
- Norman, D. A., 75
- Notch filters, 178, 182, 186, 315
 - frequency response functions, 191
 - temporal distortions from, 204–207, 206f
- Null hypothesis, acceptance or rejection
 - of, 253
- Number of trials, and signal-to-noise ratio, 123, 133–134
- Nunez, P. L., 34, 107
- Nyquist theorem, 127, 176
- Oddball experiment, 7
 - signal averaging in, 134
- Offline filtering, recommendations for, 181, 185, 186–187
- Offset time, filters affecting, 183, 183f
- Ohms, 334
 - in impedance measurements, 119
- Ohm's law, 166, 335
- Olfactory responses, 40
- On-line averaging, 317
- Onset latency or time, 66
 - differences measured between two conditions, 249
 - filters affecting, 183, 183f
 - of lateralized readiness potential, 85
 - measurement of, 247–249
- Operator dependence of equivalent current
 - dipole localization, 275, 277
- Orientation of dipoles, averaging of, 31
- Oscillations
 - amplitude, measurement of, 142–143
 - artifactual, caused by filters, 183f, 184
 - voltage, sources of, 113
- Osman, A., 80, 86b, 248
- Osterhout, L., 46
- Overlap, 145–149, 146f
 - adjacent response (ADJAR) filters for, 149
 - in analysis of multiple peaks, 262, 263
 - area-based measures in, 140
 - difference waves for, 91, 94–95
 - and expansion of time between stimuli, 148
 - high-pass filtering of, 149
 - isolation of components in, 247
 - management of, 148–149
 - in mean amplitude measures, 235
 - in peak amplitude measures, 232–233
 - simulation of, 148
 - subtraction of, 149
- Overshoots caused by filters, 218f, 219–220

- p-values
 - and .05 criterion, 250
 - adjustment in violation of ANOVA assumptions, 259–260
- P1 component, 10–11
 - visual, 36
 - modality-specific, 35
- P2 component, 10–11
 - amplitude measurements, 263
 - visual, 37
- P3 component, 10–11, 42–45, 339n
 - amplitude of, 43–44
 - in attentional blink context, 93–94
 - context updating hypothesis of, 42–43
 - discovery of, 5
 - elicited by bright and dim stimuli, 73, 252
 - latency of, 44–45
 - modality-specific, 35
 - P3a, 42
 - P3b, 42
 - signal averaging in oddball experiment, 134
 - and stimulus evaluation time, 93–94
 - and uncertainty, 42–43, 48
- P100 component, 11b
- P300 component, 11b
- P600 component, 46
- Partial information transmission, study of, 80–87, 84f
- Pascual-Marqui, R. D., 284
- Patterson, T., 248, 249
- Peak(s), 10–11
 - artifactual, added by filters, 179
 - compared to components, 52, 230, 233, 239
 - multiple, analysis of, 262–263
 - relation to latent components, 51–57, 53f
 - shapes of, 53f, 54
 - X-within-Y-of-peak function, 168
- Peak amplitude, 139, 229
 - compared to mean amplitude, 73
 - in filtered waveforms, 232
 - local, 231, 341n
 - measurement of, 229, 230–234
 - noise affecting, 231–232
 - as nonlinear measure, 232, 233
 - simple, 231, 341n
- Peak-based measures compared to area-based, 139–140
- Peak latency, 22–23, 52
 - local, 238
 - measurement of, 237–239
 - noise affecting, 238, 241
 - as nonlinear measure, 238–239
 - precautions with, 239
- Peak-to-peak amplitude
 - in electrooculogram, 155–156, 157
 - measurements of, 237
 - in saccade detection, 165
 - in slow voltage shifts, 167
- Pelli, D. G., 324, 330
- Pernier, J., 32, 58, 111
- Perrin, F., 32, 58, 111, 321
- PET scans. *See* Positron-emission tomography
- Phase(s)
 - of frequencies, 191
 - plots of, 189, 340n
 - response function of filters, 179
 - shift caused by filters, 181
- Phillips, C., 285
- Physical stimulus confounds
 - avoidance of, 74
 - effects of, 67–74, 70b–71b
- Picton, T. W.
 - on auditory selective attention, 76
 - on brain electrical source analysis, 271
 - on ERP components, 35, 59
 - on impedance, 167
 - on N1 component, 39
 - on N2 family, 40
 - on overlap, 149
 - on P3 family, 43
 - on plotting ERP data, 225
 - on skin potentials, 121
 - on tin electrodes, 117
- Pixels, 325
- Platt, J. R., 295
- Plonsey, R., 34, 269
- Plotting ERP data
 - examples of, 226–227, 226f
 - line types in, 228
 - multiple electrode sites in, 225–226, 228
 - negative upward and positive downward, 9, 10b
 - recommendations for, 225–229, 321
 - voltage and time scales in, 226

- Polarity
 - and definition of ERP component, 58, 59
 - reversal in eyeblinks, 159–160, 159f, 161
- Polich, J., 18, 42, 43, 117
- Pooled error term, use of, 261
- Pop-out stimuli, 14
- Popper, K., 295
- Positive-downward plotting, 9
- Positron-emission tomography (PET)
 - compared to ERP source localization, 289–292
 - compared to event-related potentials, 16
 - compared to other recording techniques, 24t, 267
- Posner, M. L., 47
- Post-auricular reflex, 324
- Postsynaptic potentials, 28
 - summation of, 29–31
- Potential(s), 40, 101–104, 333
 - event-related. *See* Event-related potentials (ERPs)
 - readiness, 47–48
 - skin, 121
 - vertex positive, 37–38
- Potter, M. C., 88
- Prestimulus interval, and baseline voltage, 236
- Primary auditory cortex, 38
- Primary visual cortex, 35–36
- Principal components analysis (PCA), 58, 59–60, 242, 263
- Pritchard, W. S., 43
- Probabilistic approaches to localization, 292–294
- Probability, and P3 amplitude, 44
- Psychological confounds, effects of, 68
- PsychToolbox, 330
- Raster beam, 325, 326f
- Raymond, J. E., 87, 88
- Reaction time. *See also* 50 percent area latency measure
 - in bright or dim conditions, 71, 74
 - compared to ERP latencies, 243–247, 244f
 - differences, 22, 23
- Readiness potential, 47–48
 - lateralized, 48, 65
- Real-time control in programming, 322
- Real-time monitoring, 316, 317
- Recliner, 169, 306
- Recording, 99–129
 - active and reference electrodes in, 101–112
 - amplification in, 128–129
 - continuous, 315
 - digitization process in, 124–126
 - direct coupled (DC), 126, 185
 - in saccades, 163, 166
 - and electrical noise in environment, 112–116
 - electrodes and impedance in, 116–124
 - epoch-based, 316
 - filters in
 - high-pass, 125–126
 - low-pass, 127–128
 - importance of clean data in, 86–87, 99–101, 185
 - interactions with subjects in, 311b–312b
 - sampling period in, 127
- Recording chamber, 309
- Recursive filters, 200
- Reference electrodes, 103, 104–112, 105f, 308
 - artifacts and noise sources in, 170
 - average across all electrodes, 109–111, 110f
 - mastoid process sites, 106–107, 308
 - average deviation, 107–108
 - linked mastoids reference, 107
 - site selections, 104–112, 105f
 - alternatives to, 109–112, 110f
 - criteria for, 106
- Reflexes, stimulus-related, 324
- Refresh rate of CRT monitor, 325
- Regan, D., 2, 35
- Reliability of ERP waveforms, 17–21, 19f
- Replication as best statistic, 250–251, 251b
- Requin, J., 48
- Residual variance, 272
- Resistance, 334, 335
 - of skull, 33, 339n
- Resource allocation, and P3 amplitude, 44
- Response density waveforms, 246–247
- Response devices, types of, 306–307
- Response-locked averaging, 138f, 140, 307, 320
 - baselines in, 237
- Response-related ERP components, 47–49

- Retina, integration time of, 327, 341n
- Riehle, A., 48
- Ritter, W., 6, 37, 41, 47
- Robson, T., 324
- Rohrbaugh, J. W., 49
- Rossion, B., 38
- Ruchkin, D. S., 175
- Rugg, M. D., 35, 285
- Rules for experimental design, 52–57, 74, 92, 96–97
- Running average filters
 impulse response function of, 210f, 211–212, 213
 temporal distortion from, 213–214
- Saccades
 detection and rejection of artifacts, 162–166
 electrooculogram in, 163, 164f
 visual ERP responses in, 163
- Sampling period, 127
- Sampling rate, 127
 and cutoff frequency, 128
- Sanford, A. J., 49
- Saturation, amplifier, 167–168
- Scalp current density (SCD), 111
- Scalp distribution
 in brain electrical source analysis (BESA), 272
 and definition of ERP component, 58, 59
 distortion of, 236–237
 in experimental effects or in raw ERP waveforms, 55
 and inverse problem, 269
 topographic maps of, 321
 voltage at different neural generator sites affecting, 254–257, 256f, 258
- Scalp ERPs, 29–31, 39f
- Schendan, H. E., 38
- Scherg, M., 117, 171, 172, 271
- Schmidt, D. M., 285, 294
- Schmolsky, M. T., 275
- Schultz, D. W., 80
- Schwent, V. L., 76
- Scientific inference, principles of, 295–4297
- Seating arrangements for subjects, 169, 305–306
- Seeded dipoles, 276
- Selective attention, auditory, 75–80, 77f, 340n
- Semantics
 affecting ERP components, 45
 mismatch in
 in attentional blink context, 89
 difference waves in, 54
- Sensory disorders, steady-state response
 in, 151
- Sensory responses
 auditory, 38–49
 evoked by nontarget stimuli, 78
 visual, 35–38
 in eyeblinks and eye movements, 173
- Sereno, M. I., 45, 285
- Setting up ERP lab, 303–332. *See also*
 Laboratory setup
- Shapes of peaks and components, 53f, 54
- Shapiro, K. L., 43, 64, 87, 88, 89–94, 149
- Sheatz, G. C., 4
- Shibasaki, H., 48
- Shielding
 of cables, 114, 116, 305, 308, 312b
 of headphones, 324
- Shifts
 latency, 181
 phase, 181
 slow voltage, 166–167, 178, 182
- Shocks
 from improper grounding, 101–102
 for somatosensory stimulation, 324
- Side lobes with running average filter, 211
- Signal averaging. *See* Averaging
- Signal-to-noise ratio, 16
 in averaging, 133–134
 of difference waves, 65
 number of trials affecting, 123, 133–134
 for target and nontarget waveforms, 69, 71
- Silver/silver-chloride electrodes, 117
- Simple peak amplitude, 231, 341n
- Simson, R., 41
- Simulated head, 114–116, 115f
- Simulation study of equivalent current
 dipole localizations, 278–280, 341n
- Single-unit recordings, 28
- 60-Hz noise, 113
 filtering of, 188f, 190, 202f, 203–204
- 60-Hz notch filters, temporal distortions
 from, 204–207, 206f

- Skin potentials, 121, 164f, 166–167
 - high-pass filters for, 125, 178, 182
- Slow voltage shifts, 166–167, 178, 182
- Snyder, A., 267
- Software
 - for data analysis, 318–322
 - data from simulated head, 116
 - for digitization, 315–318
 - testing of, 317–318
 - for stimulus presentations, 322, 330
- Soltani, M., 42
- Somatosensory stimulation, 40
 - artifacts from, 324
- Sommer, W., 45
- Source analysis procedures in artifact correction, 172
- Source localization. *See* Localization methods
- Source waveforms, 273, 274f
- Spatial layout of EEG display, 317
- Spatial resolution of recording techniques, 24t, 25–26
- Speakers, powered, 310
- Spectral averaging, time-locked, 142–145, 144f
- Sphericity, 258
- Spike density waveforms, 246
- SQUID probe, 33
- Squires, K. C., 42
- Squires, N. K., 42
- Static electricity, 102
- Statistical analyses, 250–264, 321
 - follow-up comparisons, 260–262
 - interactions between conditions and electrode sites in, 254–258, 256f
 - for multiple components, 262–263
 - normalization of data in, 257–258
 - results described in, 255b
 - standard approach in (ANOVA), 251–254
 - type I errors in, 250, 253
 - type II errors in, 253–254
 - violation of ANOVA assumptions, 250, 258–260
- Steady-state responses to stimuli, 150–151, 150f
- Step function
 - in eyeblink artifact rejection, 161, 162
 - in saccade detection, 165
 - in slow voltage shifts, 167
- Stimulus confounds
 - avoidance of, 74
 - effects of, 67–74, 70b–71b
- Stimulus evaluation time, P3 wave in, 93–94
- Stimulus-locked averages, 138f, 140
- Stimulus presentation system, 322–332
 - artifacts in, 324
 - timing of event codes in, 322–324
- Strategies for experimental design, 62–66, 94–95, 98
- Strong inference, 295
- Stroop paradigm, 21–22
- Stuss, D. T., 35
- Summation of electrical potentials, 29–31
- Sutton, S., 5
- Swaab, T. Y., 46
- Sweating, and skin potentials, 121, 166, 178
- Syndulko, K., 49
- Syntax affecting ERP components, 46
- Szücs, A., 246
- Tallon-Baudry, C., 143, 145
- Target and nontarget differences, effects of, 67–71
- Target probability, and P3 amplitude, 43
- Tearing artifact, 328
- Teder-Sälejärvi, W. A., 150f
- Temporal jitter, filtering properties of, 147
- Temporal resolution of recording techniques, 24t, 25–26
- 10/20 system for placing electrodes, 118b–119b
- Testing of digitization system, 317–318
- Text files, 317, 321
- Thayer, J. F., 262
- Thorpe, S., 66
- Time constants of filters, 179, 180f, 181
- Time delays between stimuli, and overlapping waveforms, 147, 148
- Time domain, 175, 317
 - distortions from filters, 192–193, 204–223, 206f, 210f
 - in filtering, 193–200, 194f
 - implementation of high-pass filters, 216–219, 218f
 - impulse response function in, 196–200, 198f

- relation to frequency domain, 182, 184, 187, 200–204, 201f, 202f
 - weighting function in, 195–196
- Time-locked spectral averaging, 142–145, 144f
- Timing of event codes, 322–324
- Tin electrodes, 117
- Tomberg, C., 109
- Transfer function, 178–179
- Transient responses to stimuli, 149–150, 150f
 - and filtering, 340n
- Transient waveforms represented in
 - Fourier analysis, 192
- Transmission of partial information, responses to, 80–87, 84f
- Treisman, A. M., 75
- Tucker, D. M., 47, 122, 123
- Type I errors, 250, 253
- Type II errors, 253–254

- Ulrich, R., 248, 249
- Uncertainty, and P3 amplitude, 44
- Uniqueness problem in source
 - localization, 269
- Unity impulse response function, 217, 218f
- Urbach, T. P., 257

- Van Essen, D. C., 340n
 - van Shier, H. T., 47
- Variability
 - between-subject, 17–20
 - latency, 135–139, 136f, 139f
 - within-subject, 18
- Variance, residual, 272
- Vasey, M. W., 262
- Vasjar, J., 271
- Vaughan, H. G., 6–7, 41, 47
- Verleger, R., 42
- Vertex positive potential, 37–38, 40
- Vertex site, 37
- Vertical retrace interrupt, 328
- Very early components, auditory, 38–39
- Video blanking interrupt, 328
- Video cards, frame buffers in
 - in CRT monitors, 325, 329
 - in LCD monitors, 330
- Video monitors, noise from, 113

- Video splitter, 305
- Visual cortex, primary, 35–36
- Visual evoked potential, 7
- Visual evoked response, 7
- Visual inspection in artifact detection, 156, 158
- Visual sensory responses, 35–38
- Visual stimuli presentation
 - CRT monitors in, 324–332
 - LCD monitors in, 330–332, 331f
 - software packages for, 330
 - timing of, 323, 323f
- Vitacco, D., 298
- Vogel, E. K., 22, 36, 37, 41, 43, 64, 89–94, 149
- Voltage, 333
 - absolute, 103
 - between active and reference sites, 101–104
 - ADC range for, 125
 - averaged at time points, 192f, 193–195
 - baseline, 236
 - changes with skin potentials, 121
 - deflection from eyeblinks, 153–154
 - distribution
 - in forward problem, 268
 - in inverse problem, 269
 - and impedance, 117
 - and latent components, 52, 56
 - oscillating, sources of, 113
 - prestimulus, 236
 - at single site, 103
 - slow voltage shifts, 166–167, 178, 182
- Volume conduction, 32
- von Cramon, D., 271

- Wada, M., 40
- Walter, W. G., 4, 49
- Wastell, D. G., 141
- Wauschkuhn, B., 42
- Waveforms
 - distortion by filters, 170, 182–185, 183f
 - overlapping, 145–149, 146f. *See also*
 - Overlap
 - response density, 246–247
 - source, 273, 274f
 - spike density, 246
- Weighting function for filtering, 195–196
 - reversed, 196

- Westerfield, M., 172
- Willoughby, A. R., 47
- Windowed ideal filter
 - high-pass, 220, 221f
 - low-pass, 208–209, 210f, 213
- Woldorff, M. G., 39, 69, 70b, 145, 148, 149, 214, 236
- Wood, C. C., 255, 257, 259, 285, 294
- Woodman, G. F., 22, 65
- Woody, C. D., 141
 - filter technique, 141–142
- Word identification, N400 component in, 89–93

- X-within-Y-of-peak function, 168

- Zubin, J., 5